BADGER *Wheeled* Self-Expelling Portables





Effective Class B and C fire protection

These quality wheeled fire extinguisher models are designed for single person use and operation. They are extremely versatile and ready to tackle flammable liquid and electrical equipment fire hazards. They are ideally suited for industrial applications where delicate equipment or processes require a clean extinguishing agent.

Carbon Dioxide is an effective and clean gaseous extinguishing agent that leaves no residue to clean up. These models are suitable for use on Class B and C fires.

Features:

- Heavy-duty hand wheel cylinder activation valves
- 16 inch semi-pneumatic rubber wheels
- Quick release discharge nozzle retainer
- Heavy-duty industrial discharge valve and nozzle
- UL Listed—Meets D.O.T. requirements
- Five year periodic hydrostatic test interval
- Six year warranty
- CD-50 model equipped with 15' hose length
- CD-100 model equipped with 40' hose length



Badger Fire Protection 944 Glenwood Station Lane, Suite 303, Charlottesville, VA 22901 Tel.: 434.964.3200 • Fax: 434.964.3202 • www.badgerfire.com

Technical Data: BADGER Wheeled Carbon Dioxide Self-Expelling Models

MODEL	CD50-1	CD100-1
PART NUMBER	22724	22725
CAPACITY (lb.)	50	100
CAPACITY (kg)	22.68	45.36
UL FIRE RATING	20-B:C	20-B:C
AGENT TYPE	Carbon Dioxide	Carbon Dioxide
CYLINDER MATERIAL	Steel	Steel
VALVE MATERIAL	Brass	Brass
HANDLE/LEVER MATERIAL	n/a	n/a
EXPELLANT	Carbon Dioxide	Carbon Dioxide
Operating Pressure @ 70° F	850	850
TEMPERATURE RANGE (° F)	-40 to 120	-40 to 120
TEMPERATURE RANGE (° C)	-40.0 to 48.9	-40.0 to 48.9
AGENT FLOW RATE (lb/sec)	n/a	n/a
AGENT FLOW RATE (kg/sec)	n/a	n/a
NOM. DISCHARGE TIME (sec)	30	60
DISCHARGE RANGE (ft.)	10.0	10.0 to 15.0
DISCHARGE RANGE (m)	3.85	3.65 to 4.57
UNIT HEIGHT (in.)	52	52
UNIT HEIGHT (cm)	132.1	132.1
UNIT WIDTH (in.)	21.5	32
UNIT WIDTH (cm)	54.61	81.28
UNIT DEPTH (in.)	33	33
UNIT DEPTH (cm)	83.8	83.8
SHIPPING WEIGHT (lb.)	271	446
SHIPPING WEIGHT (kg)	122.9	202.3
USCG APPROVAL	n/a	n/a

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:

SAFETY SYSTEMS TECHNOLOGY (NV), INC.

23282 Mill Creek Drive, Suite 215, Laguna Hills, California 92653 Tel. 949-583-1857 Fax 949-340-6643 http://www.safetysys.com Badger Fire Protection 944 Glenwood Station Lane, Suite 303 Charlottesville, VA 22901 Tel.: 434.964.3200 • Fax: 434.964.3202 www.badgerfire.com

May 2008

SS B-014 All Rights Reserved.

